



Designation	Shaft diameter		Dimensions													Weight
	(in)	(mm)	Ho	H	J	j	A2	A1	A	N	L	P	B	S	Z	(kg)
SSUCFB204 A		20	108	42.9	38.1	22.2	15.9	9.5	25.4	10	60.3	31	12.7	34.2	M8	0.58
SSUCFB204-12 A	3/4	20	108	42.9	38.1	22.2	15.9	9.5	25.4	10	60.3	31	12.7	34.2	M8	0.58
SSUCFB205 A		25	120.7	46	41.6	28.6	16.7	11.1	29.4	10	63.5	34.1	14.3	36.4	M8	0.73
SSUCFB205-14 A	7/8	25	120.7	46	41.6	28.6	16.7	11.1	29.4	10	63.5	34.1	14.3	36.4	M8	0.73
SSUCFB205-15 A	15/16	25	120.7	46	41.6	28.6	16.7	11.1	29.4	10	63.5	34.1	14.3	36.4	M8	0.73
SSUCFB205-16 A	1	25	120.7	46	41.6	28.6	16.7	11.1	29.4	10	63.5	34.1	14.3	36.4	M8	0.73
SSUCFB206 A		30	136.5	52.4	47.6	31.8	18.7	11.1	33.3	10	70	38.1	15.9	40.8	M8	1.13
SSUCFB206-17 A	1-1/16	30	136.5	52.4	47.6	31.8	18.7	11.1	33.3	10	70	38.1	15.9	40.8	M8	1.13
SSUCFB206-18 A	1-1/8	30	136.5	52.4	47.6	31.8	18.7	11.1	33.3	10	70	38.1	15.9	40.8	M8	1.13
SSUCFB206-19 A	1-3/16	30	136.5	52.4	47.6	31.8	18.7	11.1	33.3	10	70	38.1	15.9	40.8	M8	1.13
SSUCFB206-20 A	1-1/4	30	136.5	52.4	47.6	31.8	18.7	11.1	33.3	10	70	38.1	15.9	40.8	M8	1.13
SSUCFB207 A		35	155.6	60.3	50.8	31.8	21	14.3	37.3	13	82.6	42.9	17.5	46.4	M10	1.7
SSUCFB207-20 A	1-1/4	35	155.6	60.3	50.8	31.8	21	14.3	37.3	13	82.6	42.9	17.5	46.4	M10	1.7
SSUCFB207-21 A	1-5/16	35	155.6	60.3	50.8	31.8	21	14.3	37.3	13	82.6	42.9	17.5	46.4	M10	1.7
SSUCFB207-22 A	1-3/8	35	155.6	60.3	50.8	31.8	21	14.3	37.3	13	82.6	42.9	17.5	46.4	M10	1.7
SSUCFB207-23 A	1-7/16	35	155.6	60.3	50.8	31.8	21	14.3	37.3	13	82.6	42.9	17.5	46.4	M10	1.7